

DASH PANEL DR650

The kit includes:

- Dash panel
- 2 x 12V sockets
- 2 x water resistant switches
- Wiring set
- Tie Wraps
- 2 x screws

Tools required:

- 12mm Wrench/Ratchet-socket
- 14mm Wrench/Ratchet-socket
- 10mm Wrench/Ratchet-socket
- 4 mm Allen Key
- Phillips screw driver

Installation:

- 1. Install the 12v sockets and switches to the dash.
- 2. Connect wiring as shown in image 1.

3. Remove:

- Fairing by unscrewing the 3 phillip head bolts that hold it in place.
- . Rear, Left and right panels by unscrewing the two phillip head bolts.
- . The Seat by unscrewing the two 14mm bolts that hold it in place. Remove by pulling up and back.
- The Tank by unscrewing the two 10mm bolts that hold it in place on the rear part of the tank. Disconnect tank fuel hoses. Remove by pulling the tank up and back and remember to close the petcock.
- Handlebar mount by unscrewing the 2 nuts underneath the upper section of the triple clamp, one on each side.
- 4. Install the dash unit between the triple clamp and the handlebar mount as shown in (image 2.)
- 5. Tighten the 2 nuts underneath the upper section of the triple clamp, one on each side
- 6. Route the cables through the triple clamp and underneath the tank and tank shroud. Secure them with the provided tie wraps.
- 7. Connect cables to the battery (red positive, black negative), test power sockets and switches.
- 8. Install all the removed parts by reversing the process.

REMEMBER TO CONECT ALL THE TANK HOSES!!

Follow us on:



@aemotosports



AE Motosports

